

LTX 100 General Purpose Thermal Transfer Paper

Product Description

A premium quality thermal transfer material designed to provide outstanding printability for barcode applications. Excellent for high volume packaging applications.

Facestock Description

A highly absorbent, smudge-resistant, ultra smooth facestock. Provides excellent barcode quality and scannability with virtually all thermal transfer printers.

Test Property	Typical Values
Type	Premium Coated Thermal Transfer
Basis Weight (lbs.)	48# ± 10%
Caliper (mils)	2.9
Ribbon Compatibility.....	100 Plus™, 200 Plus™, 500 Plus™

Adhesive Description

Aggressive, rubber-based permanent adhesive for surfaces found in the packaging industry.

Test Property	Typical Values
Type	General Purpose Permanent
Application Temperature (Minimum).....	+40°F
Service Temperature Range	-20°F to +145°F

Liner Description

Test Property	Typical Values
Type	41# ± 10% Super-Calendered Kraft
Caliper (mils)	2.5 ± 10%

Recommendations

- One-year shelf life from receipt of material, if properly stored.
- Recommended storage conditions are 72°F (22°C) and 50% relative humidity.
- Good for use in: distribution, shipping, address and work-in-progress labels.

As with all pressure-sensitive materials, **LABELTRONIX®** recommends this product be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

***Please note that the above data represents expected averages with variances following industry standards. They should not be misinterpreted as minimum or absolute values.**

This specification sheet was updated and confirmed as of 10/4/01.