

LTX 200 Thermal Transfer High Gloss for General Purpose

Product Description

A high-gloss thermal transfer litho construction designed for applications requiring a "premium" look.

Facestock Description

A mirror-finished, high strength paper stock designed for quality printing with a "premium" look.

Test Property	Typical Values
Type.....	Cast-Coated Thermal Transfer
Basis Weight (lbs.).....	60# ± 10%
Caliper (mils)	3.7 ± 10%
Ribbon Compatibility.....	200 Plus™, 500 Plus™

Adhesive Description

A general purpose rubber-based, permanent packaging adhesive characterized by excellent tack and ultimate adhesion to a wide variety of surfaces, including most styrenes, polypropylenes, polyethylenes, papers and corrugates.

Test Property	Typical Values
Type.....	General Purpose Permanent
Application Temperature (Minimum)	+35°F
Service Temperature Range	-65°F to +150°F

Liner Description

Test Property	Typical Values
Type.....	42# ± 10% Super-Calendered Kraft
Caliper (mils)	2.6 ± 10%

Recommendations

- One-year shelf life from receipt of material, if properly stored.
- Recommended storage conditions are 72°F (22°C) and 50% relative humidity.
- Good for use in: retail and consumer goods, package labels and color preprinted labels requiring a "premium" look.

As with all pressure-sensitive materials, **LABELTRONIX®** recommends this product be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

***Please note that the above data represents expected averages with variances following industry standards. They should not be misinterpreted as minimum or absolute values.**

This specification sheet was updated and confirmed as of 10/2/01.