

LTX 510 Thermal Transfer Paper with Removable Adhesive

Product Description

A premium quality thermal transfer material with removable adhesive, and a coating ideal for high-density barcode applications.

Facestock Description

A highly absorbent, smudge-resistant, ultra smooth facestock. Provides excellent barcode quality and scannability with virtually all thermal transfer printers.

Test Property	Typical Values
Type.....	Premium Coated Thermal Transfer
Basis Weight (lbs.).....	49.5# ± 10%
Caliper (mils)	3.2 ± 10%
Ribbon Compatibility.....	100 Plus™, 200 Plus™, 500 Plus™

Adhesive Description

A general purpose adhesive that features moderately high tack and ultimate bond strength, while providing clean removability. This adhesive is good on curved surfaces, such as test tubes.

Test Property	Typical Values
Type.....	Removable Hot Melt Rubber
Application Temperature (Minimum)	+10°F
Service Temperature Range	-65°F to +120°F

Liner Description

Test Property	Typical Values
Type.....	42.5# ± 10% Super-Calendered Kraft
Caliper (mils)	2.5 ± 10%

Recommendations

- One-year shelf life from receipt of material, if properly stored.
- Recommended storage conditions are 72°F (22°C) and 50% relative humidity.
- Good for use in: test tubes and applications where clean removability is important.

As with all pressure-sensitive materials, **LABELTRONIX®** recommends this product be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

***Please note that the above data represents expected averages with variances following industry standards. They should not be misinterpreted as minimum or absolute values.**

This specification sheet was updated and confirmed as of 12/19/02.