

# LTX 600 Thermal Transfer Gloss White Polyester

## Product Description

A general purpose, high performance polyester label film. **LTX 600** is UL approved, when printed with a **LABELTRONIX® 200 Plus™** or **500 Plus™** ribbon under UL# MH26576. This facestock resists tearing, abrasion and heat. The gloss white surface makes label graphics easy to read.

## Facestock Description

A gloss, topcoated, thermal transfer printable, white polyester.

Test Property	Typical Values
Type	Gloss White Polyester
Caliper (mils)	2.0 ± 10%
Ribbon Compatibility	200 Plus™, 500 Plus™

## Adhesive Description

An aggressive, high performance permanent adhesive. This adhesive offers high initial tack, high shear, and high ultimate bond to a wide variety of surfaces.

Test Property	Typical Values
Type	General Purpose Acrylic
Application Temperature (Minimum)	50°F
Service Temperature Range	-40°F to 302°F

## Liner Description

Test Property	Typical Values
Type	Bleached Kraft
Caliper (mils)	3.1 ± 10%

## Recommendations

- One-year shelf life from receipt of material, if properly stored.
- Recommended storage conditions are 72°F (22°C) and 50% relative humidity.
- Good for use in: UL rating plates and nameplates, material tracking, under the hood labels, parts identification, and asset management labels.

As with all pressure-sensitive materials, **LABELTRONIX®** recommends this product be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

**\*Please note that the above data represents expected averages with variances following industry standards. They should not be misinterpreted as minimum or absolute values.**

This specification sheet was updated and confirmed as of 4/09/03.