

LTX 607 Thermal Transfer Matte White Polyester

Product Description

A general purpose, high performance polyester label film. **LTX 607** is UL/CSA approved, when printed with a **LABELTRONIX®** 100 Plus™ or 500 Plus™ ribbon under UL# MH26576. This facestock resists tearing, abrasion and heat.

Facestock Description

A matte, topcoated, thermal transfer printable, white polyester.

Test Property	Typical Values
Type.....	Matte White Polyester
Caliper (mils)	2.4 ± 10%
Ribbon Compatibility.....	100 Plus™, 200 Plus™, 500 Plus™

Adhesive Description

An aggressive, high performance permanent adhesive. This adhesive offers high initial tack, high shear, and high ultimate bond to a wide variety of surfaces.

Test Property	Typical Values
Type.....	General Purpose Acrylic
Application Temperature (Minimum)	50°F
Service Temperature Range	-40°F to 302°F

Liner Description

Test Property	Typical Values
Type.....	Bleached Kraft
Caliper (mils)	3.1 ± 10%

Recommendations

- One-year shelf life from receipt of material, if properly stored.
- Recommended storage conditions are 72°F (22°C) and 50% relative humidity.
- Good for use in: UL rating plates and nameplates, material tracking, under the hood labels, parts identification, and asset management labels.

As with all pressure-sensitive materials, **LABELTRONIX®** recommends this product be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

***Please note that the above data represents expected averages with variances following industry standards. They should not be misinterpreted as minimum or absolute values.**

This specification sheet was updated and confirmed as of 11/05/02.