

# LTX 124 Ink Jet Semi-Gloss Premium Paper

## Product Description

A semi-gloss coated paper stock designed especially for the VP2020 and LTX 800 digital ink jet printer.

## Facestock Description

A white, semi-gloss sheet specially engineered for use in VP2020 and LTX 800 on-demand ink jet printers. It couples good ink jet print quality with fast ink drying time and is ideal for applications printing variable information in conjunction with full color graphics.

Test Property .....	Typical Values
Type .....	Semi-Gloss Coated Paper Stock
Basis Weight (lbs.) .....	.60 ± 10%
Caliper (mils) .....	.3.7 ± 10%

## Adhesive Description

A versatile, general purpose permanent adhesive designed for excellent adhesion to corrugated and superior adhesion to plastics. Offers excellent initial tack without sacrificing high speed converting.

Test Property .....	Typical Values
Type .....	Emulsion Acrylic
Application Temperature (Minimum) .....	+25°F
Service Temperature Range .....	-65°F to +200°F

## Liner Description

Test Property .....	Typical Values
Type .....	40# Bleached Super-Calendered Kraft
Caliper (mils) .....	2.5 ± 10%

## Recommendations

- One-year shelf life from receipt of material, if properly stored.
- Recommended storage conditions are 72°F (22°C) and 50% relative humidity.
- Good for use in: shipping labels, primary labels and color-coded inventory labeling.

As with all pressure-sensitive materials, LABELTRONIX® recommends this product be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

**\*Please note that the above data represents expected averages with variances following industry standards. They should not be misinterpreted as minimum or absolute values.**

This specification sheet was updated and confirmed as of 12/05/05.