

LTX 125 Ink Jet High Gloss Premium Paper

Product Description

A white high gloss paper stock designed especially for the VP2020 and LTX 800 digital ink jet printer. This material works especially well when printing variable information in combination with full color graphics.

Facestock Description

A white, high gloss, coated sheet specially engineered for use in VP2020 and LTX 800 on-demand ink jet printers.

Test Property	Typical Values
Type.....	Coated High Gloss Paper Stock
Caliper (mils)	3.7 ± 10%

Adhesive Description

A versatile general purpose permanent adhesive.

Test Property	Typical Values
Type.....	Acrylic
Application Temperature (Minimum)	+25°F
Service Temperature Range	-65°F to +200°F

Liner Description

Test Property	Typical Values
Type.....	42# ± 10% Super-Calendered Kraft
Caliper (mils)	2.5 ± 10%

Recommendations

- One-year shelf life from receipt of material, if properly stored.
- Recommended storage conditions are 72°F (22°C) and 50% relative humidity.
- Good for use in: primary and product labeling.

As with all pressure-sensitive materials, LABELTRONIX® recommends this product be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

***Please note that the above data represents expected averages with variances following industry standards. They should not be misinterpreted as minimum or absolute values.**

This specification sheet was updated and confirmed as of 12/05/05.