

LTX 123A General Purpose Thermal Transfer Paper

Product Description

A quality thermal transfer material designed to provide high quality printability for barcode and text applications. Ideal for high volume packaging applications

Facestock Description

A matte-coated paper featuring ultra smooth high strength and smudgeproof performance.

| Test Property | Typical Values |
|----------------------|-------------------------|
| Type | Coated Thermal Transfer |
| Basis Weight (lbs.) | 46# ± 10% |
| Caliper (mils) | 2.7 ± 10% |
| Ribbon Compatibility | 100 Plus™, 220 Formula™ |

Adhesive Description

General purpose permanent acrylic. Excellent adhesion to many substrates, especially corrugated. Good low temperature performance.

| Test Property | Typical Values |
|-----------------------------------|-------------------|
| Type | Acrylic Permanent |
| Application Temperature (Minimum) | +32°F |
| Service Temperature Range | -4°F to +176°F |

Liner Description

| Test Property | Typical Values |
|----------------|---------------------|
| Type | 2.5 mil-White Kraft |
| Caliper (mils) | 2.5 ± 10% |

Recommendations

- One-year shelf life from receipt of material, if properly stored.
- Recommended storage conditions are 72°F (22°C) and 50% relative humidity.
- Good for use in: distribution, shipping, address and work-in-progress labels.

As with all pressure-sensitive materials, LABELTRONIX® recommends this product be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

***Please note that the above data represents expected averages with variances following industry standards. They should not be misinterpreted as minimum or absolute values.**

This specification sheet was updated and confirmed as of 04/01/09.