

# LTX 150 Thermal Transfer "Cover-Up" with Opaque Adhesive

## Product Description

---

A premium coated thermal transfer material with an opaque barrier coating. This opaque coating allows LTX 150 to be an effective "correction label stock".

## Facestock Description

---

A highly absorbent, smudge-resistant, ultra smooth facestock.

Test Property .....	Typical Values
Type.....	Premium Coated Thermal Transfer
Basis Weight (lbs.).....	50# ± 10%
Caliper (mils) .....	3.0 ± 10%
Ribbon Compatibility.....	100 Plus™, 220 Formula™, 500 Plus™

## Adhesive Description

---

An aggressive permanent rubber adhesive with high initial tack. This adhesive features the ability to stick to a wide variety of "difficult to adhere to" surfaces. Adhesive and facestock combination provide at least 75% opacity to allow for application over text or barcodes.

Test Property .....	Typical Values
Type.....	Opaque Cover-Up Permanent
Application Temperature (Minimum) .....	+25°F
Service Temperature Range .....	-65°F to 220°F

## Liner Description

---

Test Property .....	Typical Values
Type.....	40# ± 9% Super-Calendered Kraft
Caliper (mils) .....	2.5 ± 10%

## Recommendations

---

- One-year shelf life from receipt of material, if properly stored.
- Recommended storage conditions are 72°F (22°C) and 50% relative humidity.
- Good for use in: applications requiring a "cover-up" label, "fix" problem barcodes or general product identification.

As with all pressure-sensitive materials, **LABELTRONIX®** recommends this product be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

**\*Please note that the above data represents expected averages with variances following industry standards. They should not be misinterpreted as minimum or absolute values.**

This specification sheet was updated and confirmed as of 01/05/07.